

SMUD LED Refrigerated and Frozen Food Case Lighting Program Qualified Product list

February 24, 2010

Manufacturer	Product #	Length (ft)	End bar or center bar fixture?	Color Temp (K)	Approved as a dimmable system?	Rebate per door
1 Source Electrical Contractors, Inc.	1LB56(L/R)24V12W35KBK	5	end	3700	no	\$100
1 Source Electrical Contractors, Inc.	1LB56M24V24W35KBK	5	center	3700	no	\$100
1 Source Electrical Contractors, Inc.	2LB56(L/R)24V12W41KBK	5	end	4100	no	\$100
1 Source Electrical Contractors, Inc.	2LB56M24V30W41KBK	5	center	4100	no	\$100
1 Source Electrical Contractors, Inc.	1LB68(L/R)24V15W35KBK	6	end	3600	no	\$100
1 Source Electrical Contractors, Inc.	1LB68M24V30W35KBK	6	center	3600	no	\$100
1 Source Electrical Contractors, Inc.	2LB68(L/R)24V15W41KBK	6	end	4100	no	\$100
1 Source Electrical Contractors, Inc.	2LB68M24V30W41KBK	6	center	4100	no	\$100
Innovative Lighting Inc. EcoBrite	EcoBrite 750-5260-1	5	both	4005	no	\$100
Innovative Lighting Inc. EcoBrite	EcoBrite 750-5272-1	6	both	4005	no	\$100
Efficient Lights LLC	585-15L-0024	5	both	4005	no	\$100
Efficient Lights LLC	699-18L-0024	6	both	4005	no	\$100
ElectraLED	LS-C5-4200 CB	5	center	4334	no	\$100
ElectraLED	LS-C5-4200 EB	5	end	4334	no	\$100
ElectraLED	ELS-C5-3500K	5	center	3527	yes (1)	\$120
ElectraLED	ELS-C5-4200K	5	center	4311	yes (1)	\$120
ElectraLED	ELS-R(L) 5-3500K	5	end	3546	yes (1)	\$120
ElectraLED	ELS-R(L) 5-4200K	5	end	4302	yes (1)	\$120
ElectraLED	ELS-C6-3500K	6	center	3527	yes (1)	\$120
ElectraLED	ELS-C6-4200K	6	center	4311	yes (1)	\$120
ElectraLED	ELS-R(L) 6-3500K	6	end	3546	yes (1)	\$120
ElectraLED	ELS-R(L) 6-4200K	6	end	4302	yes (1)	\$120

**SMUD LED Refrigerated and Frozen Food Case Lighting Program
Qualified Product list**

February 24, 2010

Manufacturer	Product #	Length (ft)	End bar or center bar fixture?	Color Temp (K)	Approved as a dimmable system?	Rebate per door
GE Lumination	GE-LT-306035CTR-SY	5	center	3500	yes (2)	\$120
GE Lumination	GE-LT-306035EDL/DR-SY	5	end	3500	yes (2)	\$120
GE Lumination	GE-LT-306041CTR-SY	5	center	4100	yes (2)	\$120
GE Lumination	GE-LT-306041EDL/DR-SY	5	end	4100	yes (2)	\$120
GE Lumination	GE-LT-306050CTR-SY	5	center	5000	yes (2)	\$120
GE Lumination	GE-LT-306050EDL/DR-SY	5	end	5000	yes (2)	\$120
GE Lumination	GE-LT-307035CTR-SY	6	center	3500	yes (2)	\$120
GE Lumination	GE-LT-307035EDL/DR-SY	6	end	3500	yes (2)	\$120
GE Lumination	GE-LT-307041CTR-SY	6	center	4100	yes (2)	\$120
GE Lumination	GE-LT-307041EDL/DR-SY	6	end	4100	yes (2)	\$120
GE Lumination	GE-LT-307050CTR-SY	6	center	5000	yes (2)	\$120
GE Lumination	GE-LT-307050EDL/DR-SY	6	end	5000	yes (2)	\$120
Hussmann	EcoShine 4441328	5	center	3500	no	\$100
Hussmann	EcoShine 4441329	5	end	3500	no	\$100
Hussmann	EcoShine 4441330	5	center	4100	no	\$100
Hussmann	EcoShine 4441331	5	end	4100	no	\$100
Hussmann	EcoShine 4441394	5	center	3500	no	\$100
Hussmann	EcoShine 4441395	5	end	3500	no	\$100
Hussmann	EcoShine 4441396	5	center	4100	no	\$100
Hussmann	EcoShine 4441397	5	end	4100	no	\$100
Hussmann	EcoShine 4441601	5	center	3500	no	\$100
Hussmann	EcoShine 4441602	5	end	3500	no	\$100

SMUD LED Refrigerated and Frozen Food Case Lighting Program Qualified Product list

February 24, 2010

Manufacturer	Product #	Length (ft)	End bar or center bar fixture?	Color Temp (K)	Approved as a dimmable system?	Rebate per door
Innovative Lighting Inc.	EcoBrite 750-5260-1	5	both	4100	no	\$100
Innovative Lighting Inc.	EcoBrite 750-5272-1	6	both	4100	no	\$100
LED Power	DFB30L-276-35K-100-24	5	center	3500	no	\$100
LED Power	DFB30L-276-35K-100-24-Lens	5	center	3500	no	\$100
LED Power	DFB30L-276-41K-100-24	5	center	4100	no	\$100
LED Power	DFB30L-276-41K-100-24-lens	5	center	4100	no	\$100
Philips	LFM300 # 929000467013	5	center	4100	no	\$100
Philips	LFM300 # 929000467113	5	end	4100	no	\$100
Philips	LFM300 # 929000467413	6	center	4100	no	\$100
Philips	LFM300 # 929000467513	6	end	4100	no	\$100
Q-Technology Inc.(3)	Crossfire #5160-120-L / R	5	end	4300	no	\$100
Q-Technology Inc.(3)	Crossfire #5160-120-C	5	center	5400	no	\$100
Q-Technology Inc.(3)	Crossfire #6160-120-L / R	6	end	4300	no	\$100
Q-Technology Inc.(3)	Crossfire #6160-120-C	6	center	5100	no	\$100

(1) Approval for ElectraLED as a dimming system is contingent upon use with ELS-C-1200 dimming module and WattStopper FS-705 sensors

(2) Approval for G.E. Lumination products as a dimming system is contingent upon use of the listed fixtures plus the following components:

- LED Driver: GE-PS1800NCMUL-SY; sensor power pack: Watt Stopper® BZ-100WM; sensor: Watt Stopper® FS-705
- LED Driver: GE-PS1800NCMUL-SY; sensor power pack: Sensorswitch® MP-20-RJ; sensor: Sensorswitch® RA-15

(3) The Watts per door for this product varies depending on whether two end bars or one center bar fixture is used for the center mullion.

The information in this table is provided by SMUD as a service to our customers. SMUD does not endorse products or manufacturers. Mention of any particular product or manufacturer in this table should not be construed as an implied endorsement.